



TECHNICAL DATA SHEET (TDS)

VH602 CEMEX^{pro} - GROUT AND CEMENT RESIDUE REMOVER

1. PROPERTIES

VH602 grout and cement residue remover contains acid. Removes all grout residues and building-site dirt. Eliminates any saline efflorescence from terracotta. Removes lime deposits from floors, wall tiles (showers), and bathroom fixtures. Removes rust stains.

ADVANTAGE:

Does not emit fumes that are harmful to users or the environment; a welcome substitute to muriatic acid. Does not alter the surface color or appearance. Cleans without damaging surfaces. Do not harm aluminum or steel trims. Multi-purpose; terracotta, porcelain stoneware, and acid-resistant stone Dual use; according to dilution, can be used as either a detergent or a descaler.

2. APPLICATION AREAS

Apply on floors including terracotta, wall tiles and bathroom fixtures.

3. INSTRUCTIONS FOR USE

Dilution: 1:5 - 1:10 depending on the type of soil to be removed;

1. Spread with a single-disc professional cleaner or rag and leave to act for a few minutes.
2. Clean using a single-disc professional cleaner fitted the most appropriate disc (e.g.: brown for terracotta) or a floor cleaning brush
3. Vacuum or wipe up residue
4. Rinse with plenty of water

ATTENTION!

If some areas are still not completely clean, wash again with more concentrated solution. Do not use VH602 on glossy or preplaced marble and in general on acid-sensitive materials (E.g. black slate)

Always test in a small inconspicuous area to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application.

Make sure surface is clean, dry and free of waxes and coatings.

Mask off and protect any baseboards or adjacent areas to avoid splashing and overspray onto surfaces not intended to be treated.

4. COVERAGE

Terracotta	: 1:5	20 m ²
------------	-------	-------------------



Natural stone	: 1:10-1:5	20-35 m ²
Ceramic porcelain tiles	: 1:5	40 m ²

5. TOOLS REQUIRED FOR APPLICATION

brush, professional cleaning machine, cleaning pad, vacuum.

6. PACKAGING

PRODUCT CODE	VOLUME	PACKAGE
Can	1 Lt	12
Can	5 Lt	4

7. STORAGE AND SHELF LIFE

VH 602 must be stored in airtight original containers at temperatures not exceeding 30° C and protected from direct sunlight and direct source of heat. If stored properly the shelf life is 24 month.

8. CAUTION

- Irritating to eyes and skin

9. SAFETY MEASURES

- Keep out of reach of children

10. TECHNICAL DATA

Appearance	: Clear Liquid
Odor	: Typical
Density	: 1.03 ± 0,02 g/cm ³
pH	: 2
Type	: Acid based