

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

#### PART 1: IDENTIFICATION OF SUBSTANCE/MIXTURE AND COMPANY/DISTRIBUTOR

##### 1.1. Identification of Substance/Mixture:

Product name : WATERSTOP Water Repellent Sealer

Product code : A15

##### 1.2. Identified uses and inadvisable uses of substance or mixture

Identified uses : WaterRepellency for natural stones.

Inadvisable uses : Inadvisable special uses have not been identified.

##### 1.3. Information about Material Safety Data Sheet provider

**Company name :** ELKAY KİMYASAL MADDELER SAN. TİC. A.Ş.

**Address :** Cumhuriyet Mahallesi İsmet İnönü Caddesi No.35 41420

Çayırova- Kocaeli/Turkey

[info@elkay.com.tr](mailto:info@elkay.com.tr) / [www.elkay.com.tr](http://www.elkay.com.tr)

**Telephone :** +90 262 751 21 87-88

**Fax :** +90 262 751 21 89

**GBF contact person :** Gülcan IRMAK

##### 1.4. Emergency phone number

**Emergency phone number :** ELKAY: +90 262 751 21 89

**National emergency phone :** National poison information center (UZEM): 114 Fire brigade: 110  
Emergency health services: 112

#### PART 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of substance or mixture

Classification Republic of Turkey 28848

Physical damages Flammable Liquid 3 - H226

Medical damages Akute Tox.4-H312/ Skin Irrit.2 -H315/ Akute Tox.4-H332

##### 2.2. Label ingredients

**Hazards mark:**



GHS02



GHS07

**Warning word :** Attention

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

**Hazards phrases:** **H226** : Flammable liquid and vapor.  
**H312** : Harmful in contact with skin.  
**H315** : Causes skin irritation.  
**H332** : Harmful if inhaled.

**Precautionary phrases:** **P102** : Keep out of reach of children.  
**Precaution:** **P210** : Keep away from heat/spark/flare/hot surfaces. – No smoking.  
**P233** : Keep container tightly closed.  
**P243** : Take precautionary measures against static discharge.  
**P261** : Avoid breathing dust/fume/gas/mist/vapors/spray.  
**P271** : Use only outdoors or in a well-ventilated area.  
**P280** : Wear protective gloves/protective clothing/eye protection/face protection.

**Intervention:** **P303+P361+P353** : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
**P332+P313** : If skin irritation occurs: Get medical advice/attention.  
**P370+P378** : In case of fire: Use foam, carbon dioxide, dry powder or water mist for extinguishing.  
**P304+P340** : IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
**P314** : Get medical advice/attention if you feel unwell.

**Storage:** **P403+P235** : Store in a well ventilated place. Keep cool.

**Disposal:** **P501** : Dispose of contents/container to ... [... in accordance with local/regional/national/international

### 2.3. Other damages

Product does not contain any substance classified as PBT or vPvB.

## PART3: INFORMATION ABOUT COMPOSITION/INGREDIENTS

### 3.1. Substances

-None

### 3.2. Mixtures

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

Substance	C.A.S No-	EINECS	Concentration %	SEA T.C. 28848	
				Class, H Phrases*	
Xylene	1330-20-7	215-535-7	75-80	Flam. Liq. 3	H226
				Akute Tox.4	H312
				Skin Irrit.2	H315
				Akute Tox.4	H332

#### PART4: FIRST AID MEASURES

##### 4.1. Description of first aid measures

**Eyes** : If any, remove contact lens and rinse with plenty of water for 15 minutes by opening the eyelids. Seek medical attention if irritation persists.

**Skin** : Take off contaminated clothes, rinse with plenty of water. Seek medical attention if irritation persists.

**Ingestion:** Seek medical attention. If the patient is conscious, rinse the mouth thoroughly with plenty of water, and make him/her to drink several glasses of water or milk. Do not induce vomiting unless stated by medical staff. Never give anything to mouth of unconscious person. If vomiting occurs, help vomiting by turning head of patient to the right side in order that respiratory tracts remain open.

**Inhalation:** Take patient to fresh air. Loose the clothes squeezing tightening the body (tie, collar, belt etc.) by seating in a comfortable position to breathe. Seek immediate medical attention in case of respiratory distress.

**Protection of First Aid Officials:** First aid personnel should wear appropriate protective equipment during recovery.

Performing artificial respiration by mouth can be dangerous for first aid personnel.

##### 4.2. Acute and subsequent important symptoms and effects

**General information:** See Part 11 for additional information about health hazards. The severity of described symptoms may vary depending on concentration and duration of exposure.

**Eyes** : It causes irritation.

**Skin** : It causes rash and swelling.

**Ingestion** : It causes irritation. In case of ingestion, it has loss of aspiration.

**Inhalation** : Irritation, coughing, difficulty in breathing, chest tightness. Risk of serious damage to health in long inhalations. It is suspected to cause damage on unborn child.

##### 4.3. First marks for medical attention and special treatment requirement

Information to be provided to the doctor: apply the symptomatic treatment.

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

#### PART5: FIRE FIGHTING MEASURES

##### **5.1. Fire extinguishers**

Suitable fire extinguishing materials: Use alcohol resistant foam, carbon dioxide, dry powder or water mist. Unsuitable fire extinguishing agents because of safety: High pressure water jet

##### **5.2. Specific hazards arising from substance or mixture**

Specific hazards : Containers can explode severely when heated, because excessive pressure arises within it. Vapors can create explosive mixtures with air.

Hazardous combustion products: In case of fire, it can release hazardous gasses or vapors (such as carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)).

##### **5.3. Advices for firefighting teams**

**Protective measures which should be taken during fire extinguishing:** Discharge the area. Avoid breathing fire gasses and vapors. Before entering indoor areas, ventilate these areas. Cool containers exposed to heat with water spray and if there is not any risk, take these containers to elsewhere other than fire area. Avoid discharge / spillage to the aquatic environment. If there is a danger of water pollution, inform the relevant authorities.

Special protective equipment for fire extinguishing teams: Wear positive pressure self-contained closed-circuit breathing apparatus and suitable protective clothing.

#### PART6: ACCIDENTAL RELEASE MEASURES

##### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Any action involving personal risk should not be taken before receiving proper training. Keep away unnecessary and unprotected persons from spillage. Wear protective clothes as indicated in Part 8 of this Material Safety Data Sheet. Purify yourself thoroughly after dealing with a spillage. Ensure that procedures and emergency trainings are provided for cleaning and disposal of wastes in place. Do not touch spilled material or do not walk on it. Discharge the area. Ensure sufficient ventilation. No smoking and do not use fire, spark or other sources of ignition near spillage. In case of insufficient ventilation, wear suitable respirator.

##### **6.2. Environmental precautions**

Environmental measures: Avoid spilling into sewer, overground and underground waters, soil. Big Spillages: If environmental pollution occurs (sewer, water sources, soil or air) inform the relevant authorities.

##### **6.3. Methods and materials for protection and cleaning**

Spillage : Wear protective clothes as indicated in Part 8 of this Material Safety Data Sheet.  
Cleaning : Do not smoke, do not use fire, spark or one of other sources of ignition near

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

Methods: spillage. Collect the spillage and absorb it with sand, soil or other non-flammable substance. Place waste into labeled and sealed containers. Clean contaminated articles and areas thoroughly by considering environmental regulations. Wash contaminated area with plenty of water. Dangerous for environment. Do not discharge into the sewer.

#### **6.4. References to other parts**

All kinds of information about personal protection and disposal are provided in the Parts 8 and 13.

### **PART7: HANDLING AND STORAGE**

#### **7.1. Precautions for safe handling**

Using precautions : Ensure good ventilation. Wear protective clothes as indicated in Part 8 of this Material Safety Data Sheet. Keep away from foods, drinks and animal feeds. In order to minimize spillages, handle all packages and containers carefully. Keep away from heat/spark/flame/hot surfaces - No smoking. Substance flamed/exploded during use can form vapor-air mixture. Vapors can accumulate on the ground and within low-based areas. Use only explosive resistant and non-flammable material. It has doubt of causing damage on unborn child. If there is any exposure risk, pregnant or breastfeeding women should not work with this product. Avoid spilling on the aquatic environment. Do not handle before reading and understanding all precautionary phrases. Do not handle broken packages without protective equipment. Do not use empty containers again. When it is used, keep container tightly closed. Recommendations In case the skin is contaminated, wash immediately. Take off contaminated concerning general clothes and wash before use again. Do not eat and drink while using this occupational product. Wash your hands before eating, smoking and going to toilet. hygiene: Change work clothes every day before quitting the workplace.

#### **7.2. Conditions for safe storage including disagreements**

Storage measures: Keep only in its original container. Keep the container tightly closed, in a cool and well-ventilated ambient. Remove all sources of ignition. Take measure against static electricity discharges.

#### **7.3. Definite final uses**

It is stated in Part 1.2 in a detailed manner.

### **PART8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **8.1. Control parameters**

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

#### Occupational exposure limits

Xylene

Limit value (TWA 8 - hours) : 50 ppm 221 mg/m<sup>3</sup> (skin)

Limit Value (STEL 15 - minutes) : 100 ppm 442 mg/m<sup>3</sup> (skin)

Xylene

PNEC Fresh water ; 0.327mg/l  
Sea water ; 0.327 mg/l  
Freshwater sediment; 12.46 mg/l  
Sediment sea water; 12.46 mg/l  
Soil; 2.31 mg/kg

DNEC Employees - Inhalation; Acute/Short-term exposure-systematic effect: 289 mg/m<sup>3</sup>  
Employees - Inhalation; Acute/Short-term exposure-local effect: 289 mg/m<sup>3</sup>  
Employees - Dermal; Long-term exposure - systematic effect: 289 mg/kg  
Employees - Inhalation; Long-term exposure - systematic effect: 77mg/m<sup>3</sup>  
General population - Inhalation;Acute/Short-term exposure- systematic and local effect:174.25 mg/m<sup>3</sup>  
General population - Inhalation;Acute/Uzun-term exposure dermal effect: 108 mg/m<sup>3</sup>  
General population -;Inhalation Long-term exposure systematic effect: 14.8 mg/kg  
General population - Oral; Long-term exposure systematic effect: 1.6 mg/kg

#### 8.2. Exposure controls

##### 8.2.1. Suitable engineering Controls

Ensure sufficient ventilation. In order to minimize exposure of employees, apply process protection methods, local discharge ventilation and other technical controls as a main method. If exposure of employees can not be checked sufficiently with technical control measures, personal protective equipment should be used.

##### 8.2.2 Personal Protective Equipment



## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

<b>Protection of Hands</b> TS/EN	In order to protect hands against chemicals, gloves should comply with 374 Standard. Gloves manufactured from nitrile rubber should be used (material thickness > 0,1 mm, overflowing time < 30s). In case of long-term contact, protective gloves manufactured from butyl rubber are recommended. (material thickness > 0,7mm, overflowing time more than 60 minutes) Check whether gloves maintain their protective properties during the use according to data stated by glove producer, and if any deterioration is determined, change gloves as soon as possible.
<b>Skin Protection</b>	Wear suitable protective clothes.
<b>Eye Protection</b>	Wear protective goggles.
<b>Respiratory Protection</b>	When there is no sufficient ventilation, use suitable respiratory mask. Be careful that respirator is placed thoroughly, and replace the filter regularly. Gas filters and combined filter cartridges should comply with TS/EN 14387 Standard. Full face masks with replaceable filter cartridge should comply with TS/EN 136 Standard. Half or quarter face mask respirators with replaceable filter cartridges should comply with TS/EN 140 Standard.
<b>Environmental Exposure Controls</b>	Conformity of ventilation emissions and business process equipments with environmental protection regulations should be controlled.

#### PART9: PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1. Information about basic physical and chemical properties

Appearance	Liquid
Color	Clear, colorless liquid
Odor	Characteristic
Odor threshold	No available information
pH	5,5
Melting point	-47.4°C (-53.3 F)
Boiling point	138.5
Flash point	30°C (86 F)
Evaporation rate	No available information
Flammability (solid, gas)	No available information
Upper/Lower flammability or explosive limits	No available information
Vapor pressure	0.9 kPa (20°C)
Vapor density	3.7 (air = 1)
Solubility	Insoluble in water.
Partition coefficient: n-octanol/water	No available information
Auto-ignition temperature	500 - 500°C

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

Viscosity	No available information
Explosive properties	No available information
Oxidizing properties	No available information

#### **9.2. Other information**

No available information

### **PART10: STABILITY AND REACTIVITY**

#### **10.1. Reaction**

Reaction under  
There is no risk to enter into reaction with other substances under normal use conditions.

#### **10.2. Chemical stability**

Stability  
Stable under normal use and storage conditions.

#### **10.3. Possibility of harmful reaction**

Possibility of harmful reaction  
Its vapors can form explosive mixtures with air. It can react with oxidizing agents.

#### **10.4. Conditions to avoid**

Conditions to avoid  
Avoid heat, flame and other sources of ignition. Formation of static electricity and sparks should be prevented. Containers can explode severely when heated, because excessive pressure occurs.

#### **10.5. Substances to avoid**

Substances to avoid  
Avoid acids and oxidizing agents.

#### **10.6. Detrimental Degradation Products**

Detrimental degradation products  
No degradation when used and stored in compliance with recommended conditions. In case of any thermal decomposition or fire, gases and vapors hazardous to health can be released.

### **PART11: TOXICOLOGICAL INFORMATION**

#### **11.1. Information about toxic effects**

##### **Xylene**

Acute toxicity LD<sub>50</sub>(Oral) 5300 mg/kg Rat

Acute toxicity LC<sub>50</sub>(Skin) 2000 mg/kg Rabbit.

Skin corrosion/irritation Touching is harmful.

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

<u>Serious eye damage/irritation</u>	It causes serious eye irritation.
<u>Respiratory Sensitization</u>	Classification criteria is not met based on available data.
<u>Skin sensitization</u>	Classification criteria is not met based on available data.
<u>Carcinogenicity</u>	Classification criteria is not met based on available data.
<u>Reproduction system toxicity Fertility</u>	Classification criteria is not met based on available data.
<u>Reproduction system toxicity developmental</u>	Classification criteria is not met based on available data.
<u>Specific target organ toxicity- Single exposure</u>	Classification criteria is not met based on available data.
<u>Specific target organ toxicity- exposure</u>	Classification criteria is not met based on available data.of <u>Repeated</u>
<u>Aspiration loss</u>	Penetration into the respiratory tract and is lethal if swallowed.
General information	Avoid contact during pregnancy / breastfeeding. Severity of identified symptoms can vary depending on concentration and duration of exposure.
Inhalation	Single exposure can cause following adverse effects: Irritation of nose, throat and respiratory tract. Respiratory distress. Cough.
Ingestion	It may cause irritation. Harmful if swallowed.
Skin contact	Redness. It irritates skin. Eye contact: It irritates eyes.

#### **PART12: ECOLOGICAL INFORMATION**

General ecological information: Do not spill in sewer, soil or waters. Mixture was classified according to Republic of Turkey 28848 Annex-I. Valid health/ecological information for chemicals listed in Part 3 are as follows.

##### **12.1. Toxicity**

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

#### Ecological information about components

##### Xylene

Fish	EC <sub>50</sub> , 96 hours 16400 ug/l,(Death)	Pimephales promelas (Minnow)
Aquatic invertebrates	EC <sub>50</sub> , 48 hours 18 mg/l,	Daphnia Water flea
Algae	EC <sub>50</sub> , 8 hours 4200 ug/l,(growth)	Green sea algae(Selenastrum capricornutum)
Other	LC <sub>50</sub> 48 hours 73000 ug/l (frog)	(Xenopus laevis)

##### **Additional information on ecology**

Biological effects: Hazard for drinking water supplies. Water, waste water, or do not let the soil.

**12.2. Persistence and degradability** Theoretical oxygen demand (ThOD) 3.125 mg / g

**12.3. Bioaccumulative potential** No data available.  
Partition coefficient: n-octanol water  
Log Pow: 3,13 Method: Experimental

**12.4. Mobility in soil** No data available. Products insoluble in water. Volatile liquid. The product contains organic solvents that can evaporate easily on all surfaces.

**12.5. PBT and vPvB Assessment results** Product does not contain any substance classified as PBT or vPvB.

**12.6. Other adverse effects** Henry constant 525 Pa \* m<sup>3</sup> / mol Method: experimental  
Distribution preferentially in air.

#### **PART13: DISPOSAL CONSIDERATIONS**

##### **13.1. Waste processing methods**

General information Do not allow to enter drains or watercourses.  
Waste formation should be minimized or waste formation should be avoided everywhere possible. Dispose of wastes and residues according to local authority and management requirements.

Waste processing methods Dispose of remaining and non-recyclable products through a licensed waste disposal institution. Contaminated package should be thrown in accordance with recycling or national waste management regulations.

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

#### **PART 14: TRANSPORT INFORMATION**

##### **14.1. UN Number**

Un No. ADR/RID: 1993  
Un No. IMDG : 1993  
Un No. IATA : 1993  
Un No. ADN : 1993

##### **14.2. Suitable UN Transport Name**

ADR/RID: Flammable Liquid N.O.S (XYLENE CONTAINS)  
IMDG : Flammable Liquid N.O.S (XYLENE CONTAINS)  
IATA : Flammable Liquid N.O.S (XYLENE CONTAINS)  
ADN : Flammable Liquid N.O.S (XYLENE CONTAINS)

##### **14.3. Transport Hazard Class(es)**

ADR/RID CODE : F1  
ADR/RID Class : 3  
Label : 3  
IMDG Class : 3  
Label : 3  
IATA Class : 3  
Label : 3  
ADN Class : 3  
Label : 3

##### **Transport Label:**



##### **14.4. Packaging Group**

ADR / RID, IMDG, IATA, ADN : III

##### **14.5. Environmental Damages**

ADR / RID : NO  
IMDG : NO  
IATA : NO

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

ADN : NO

#### **14.6. Special Measures for the User**

Hazards Identification

Number ADR/RID : 30

Special Provisions : 274-601-640E

EMS : F-E , S-E

Tunnel Restriction

Code : 3(D/E)

#### **14.7. Bulk transport according to MARPOL 73/78 Annex II and IBC code**

No suitable information.

### **PART15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environment regulation peculiar to substance or mixture

National regulations Regulation on Classification, Labeling and Packaging of Substances and Mixtures dated 11 December 2013 and numbered 28848.  
Republic of Turkey, Ministry of Environment and Forestry, Regulation on Classification, Packaging and Labeling of Dangerous Substances and Preparations dated 26 December 2008 and numbered 27092.  
Occupational Health and Safety Law No. 6331.  
Regulation on Health and Safety Measures in the Studies with Chemical Substances.  
Regulation on Use of Personal Protective Equipments in the Workplaces  
Regulation on Control of Dangerous Wastes

Chemical Safety Assessment Chemical safety assessment has not been made.

### **PART16: OTHER INFORMATION**

Classification conditions according to regulation dated 11 December 2013 and numbered 28848	FLAM. LIQ.3 Akute Tox.4 Skin Irrit. 2 Akute Tox.4	Flammable Liquid Akute Toxicity (Skin) Skin irritation Akute Toxicity (Respiratory)	Category 3 Category 4 Category 2 Category 4
---	--	--	--

**Hazards phrases:** H226 : Flammable liquid and vapor.  
H312: Harmful in contact with skin.

## MATERIAL SAFETY DATA SHEET

### WATERSTOP A15 Water Repellent Sealer

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

H315: Causes skin irritation.  
H332: Harmful if inhaled.

#### Abbreviations:

SEA	: Regulation on classification, labeling and packaging of substances and mixtures.
UZEM	: National poison information center
Cas No	: Chemical Abstracts Service
EINECS No:	A descriptive list of all substances in the European Union community market.
Un Number	: Numbers to be requested from you by international courier and airway companies if you demand to transport any material which can be considered as dangerous.
TWA	: Short-term exposure limit
STEL	: Time-weighted average exposure limit
PNEC	: Predicted No-Effect Concentration - Environmental hazards
DNEL	: Derived No-Effect Level (for people)
LD 50	: Lethal dose 50 %
LC 50	: Lethal concentration 50 %
IARC	: International Agency for Research on Cancer
PBT	: Permanent and bioaccumulative and toxic
vPvB	: Very permanent and very bioaccumulative
ADR	: European agreement concerning the international carriage of dangerous goods by road
IMDG	: International Maritime Dangerous Goods Code
RID	: Regulation on the international carriage of dangerous goods by rail
IATA(DGR)	: International air transport association dangerous goods regulation
ADN	: European agreement concerning international carriage of dangerous goods by inland waterways

Issuer of Material Safety Data Sheet:

Name/Surname: Gülcan İrmak

Address: Cumhuriyet Mahallesi İsmet İnönü Caddesi No.35 41420 Çayırova- Kocaeli/Turkey

Certificate no : GBF- A-0-2286

Date of Certificate: 23.03.2016

Date of Expiry: 23.03.2019

Information contained in this material safety data sheet are based on our current knowledge and experience and describe the product with regard to safety requirements. Information does not describe the specifications of product (product specification). Any agreed specification or conformity of product with a specific purpose cannot be relied on information contained in this material safety data sheet.



GBF NO : 60010  
Revision No : 02  
Revision Date : 01.01.2020  
Issue Date : 01.01.2014  
Page No : 1/13

Chapter I

## **MATERIAL SAFETY DATA SHEET**

### **WATERSTOP A15 Water Repellent Sealer**

It is issued in accordance with provisions of "Republic of Turkey, Ministry of Environment and Urban Planning, Regulation on Safety Data Sheets relating to Hazardous Substances and Mixtures" dated 13 December 2014 and numbered 29204.

---

Product purchaser is responsible for protection of intellectual property rights and conformity with current laws and regulations in force.